



### L8225 series spring retractable pressure wash reel

impact resistant ABS construction with SAE 100 R1 AT hose



model	hose included	connection NPT in / out	working pressure	dimensions WxLxH ( mm )	weight
L8225	15m x 6mmID ( R1 )	M1/4 " - M1/4 "	200 bar	140 x 340 x 245	10 kg
L8265	15m x 10mmID ( R1 )	M3/8 " - M3/8 "	172 bar	140 x 340 x 245	11 kg

- **Durable construction** made from high quality impact resistant ABS
- **Positive latching mechanism** automatically locks hose at desired length
- **Safety lock** prevents the hose from moving in either direction



### L8200 series spring retractable air / nitrogen reel

Enclosed plastic construction with reinforced PVC hose



model	hose included	connection BSP in / out	working pressure	dimensions WxLxH ( mm )	weight
L8230-EU	9m x 10mmID ( PVC )	M1/4 " - M1/4 "	12 bar	160 x 330 x 300	5 kg
L8250-EU	15mx10mmID ( PVC )	M1/4 " - M1/4 "	20 bar	180 x 450 x 370	7.5 kg

- **Auto-rewind**
- **Hose latching** every 450mm
- **Feeder hose** 1m length
- **Mounting bracket** for wall or ceiling installation



### Benefits of using Nitrogen for tyre inflation

- **Superior handling and increased safety**
- **Tyre inflation lasting 3—4 times longer**
- **Decreased wheel corrosion**
- **Fuel savings**

Other models available for other applications