

LevelWind

- LevelWind Technology
- Extra large swivel for best flow
- Maintainable without special tools
- Free standing base
- Durable construction
- Latching Switch
- 7 position locking brace
- Mounting bracket included
- Adjustable hose stop
- Optional mounting bracket



L8306-FZ



L8300 series spring retractable LevelWind reel

UV stabilised polypropylene construction (W 260mm x L 500mm x H 440mm)



model	application	hose included	hose material	connection in / out	working pressure	temperature deg C	weight
L8305-EU	Air	15m x 10mm ID	PVC	M1/4 " BSPT	24 bar	10 to 65	12 kg
L8305-FZ	Air	15m x 10mm ID	Flexzilla ◆	M1/4 " BSPT	20 bar	-40 to 65	12 kg
L8306-EU	Air	23m x 10mm ID	PVC	M1/4 " BSPT	24 bar	10 to 65	12 kg
L8306-FZ	Air	23m x 10mm ID	Flexzilla ◆	M1/4 " BSPT	20 bar	-40 to 65	12 kg
L8310-EU	Air	30m x 10mm ID	PVC	M1/4 " BSPT	24 bar	10 to 65	12 kg
L8335-EU	Air / Water	15m x 13mm ID	PVC	M1/2 " BSPT	20 bar	10 to 65 ■	12 kg
L8335-FZ	Air	15m x 13mm ID	Flexzilla ◆	M1/2 " BSPT	20 bar	-40 to 65	12 kg
L8345	Garden	23m x 13mm ID	PVC	M1/2 " BSPT	10 bar	5 to 60	12 kg
L8350	Potable Water	23m x 13mm ID	PVC	M1/2 " BSPT	10 bar	5 to 60	12 kg
L8351	Marine ●	18m x 16mm ID	PVC	M1/2 " BSPT	10 bar	5 to 60	15 kg
L8363-EU	oxy acetylene	15m x twin 6mm ID	Rubber	M1/4 " BSPT	14 bar	-17 to 65	15 kg

◆ Premium Hybrid Polymer Air Hose for superior flexibility / Hi-VIS colour makes hose visible in the workplace

■ 5 to 60 deg C for water application

● With stainless steel critical components

LEVELWIND™ TECHNOLOGY

A layering system that makes hose retraction smooth and easy.



Auto-rewind Auto-leveling

Other models available for other applications



Optional bench and high ceiling bracket available.