



LEVELWIND™ SERIES HOSE REELS

LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY

AUTO-REWIND

AUTO-REWIND HOSE REELS AUTO-REWIND HOSE REELS AUTO-REWIND HOSE REELS AUTO-REWIND HOSE REELS AUTO-REWIND HOSE REELS



AUTO-LEVELING HOSE REELS AUTO-LEVELING HOSE REELS AUTO-LEVELING HOSE REELS AUTO-LEVELING HOSE REELS

AUTO-LEVELING

LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY LEVELWIND™ TECHNOLOGY

Oxy-Acetylene Oxy-Fuel Air Air-Water Garden Hot Water Cold Water Potable Water Oxy-Acetylene Oxy-Fuel Air Air-Water Garden Hot Water Cold Water Potable Water Oxy-Acetylene Oxy-Fuel



Legacy™ is proud to announce the next generation of retractable hose reels. Over two decades of industry knowledge and

Garden Hot Water Cold Water Potable Water Oxy-Acetylene Oxy-Fuel Garden Hot Water Cold Water Potable Water Oxy-Acetylene Oxy-Fuel Air Air-Water Garden Hot Water



Free Standing Base:

Portable! Use free-standing or mounted on wall or ceiling ... flat base allows reel to rest on ground. Built-in handle for carrying ease!

Durable Construction

Made from durable UV-stabilized polypropylene.



Extra large swivel:

This 3/4 in. swivel reduces flow restriction and allows for maximum volume needed for your application. Lead-in hose included.

experience goes into the development of this series of reels. Featuring LEVELWIND™ TECHNOLOGY, a layering system that makes hose retraction smooth and easy.

Cold Water Potable Water Oxy-Acetylene Oxy-Fuel Air Air-Water Garden Hot Water Cold Water Potable Water Oxy-Acetylene Oxy-Fuel Air Air-Water Garden Hot Water Cold Water Potable W

AUTO-REWIND



Latching Switch:

Choose from latching hose every 3 ft. for extended use or switch to "free run" for immediate automatic rewinding.



LEVELWIND™ TECHNOLOGY:

A unique winding system that automatically layers the hose back and forth across the reel. This ensures that the hose is coiled smoothly, easily ... every time!

AUTO-LEVELING

Broad Product Line

LEVELWIND™ provides more choices for the end user through a broad line of reels that allow for more hose length and hose I.D. size options. Reels are available for air, air/water, hot wash down, cold wash down, potable water, oxy-acetylene and oxy-fuel applications. For low cost hose storage LEVELWIND™ is the answer for the automotive & industrial professional!

Visit us at www.legacymfg.com for more information on LEVELWIND™.



Adjustable hose stopper:

Increase or decrease the length of the hose that remains when hose is fully retracted.



Seven position locking brace:

Reel can swivel freely on mounting bracket up to 138° or can be locked into place using the locking brace. Up to seven different locking angles can be utilized.

Mounting Bracket Included:

Allows you to mount the reel on the wall or the ceiling.



Optional Mounting Bracket:

Mount the reel on a bench. Bracket also allows for a high wall mount (between 10 ft. and 15 ft. high) where hose points downward (optional mounting bracket is sold separately)



With a focus on the end user, Legacy™ leads the industry in manufacturing affordable hose reel products with features designed to solve problems in the field.

Cold Water Potable Water Oxy-Acetylene Oxy-Fuel Air Air-Water Garden Hot Water Cold Water Potable Water Oxy-Acetylene Oxy-Fuel Air Air-Water Garden Hot Water Cold Water Potable



L8363

Oxy / Acetylene applications

Welding Reels

Model	Application	Hose		Max. W.P.	Lead-in Hose	Discharge Hose
		Size	Material			
L8363	Oxy / Acetylene	¼ in. x 50 ft.	Reinforced Rubber Twin Hose	200 PSI	5 ft. x 9/16 in. FUNF	9/16 in. FUNF
L8366	Oxy / Fuel †	¼ in. x 50 ft.	Reinforced Rubber Twin Hose	200 PSI	5 ft. x 9/16 in. FUNF	9/16 in. FUNF

Reel inlet: 9/16 in. FUNF

†Oxy Fuel is designed for Mapp, Propane and Natural Gases

Model	Weight	Package Dimension	Cu.ft.	UPC	Harmonization
L8363	32.6 lb.	19.75 in. x 12.5 in. x 18.75 in.	2.7	0 92329 08363 5	3924.90.55.00
L8366	32.6 lb.	19.75 in. x 12.5 in. x 18.75 in.	2.7	0 92329 08366 6	3924.90.55.00

Mounting Brackets

L8300-W

Wall & Ceiling Mount Bracket

Includes a seven position locking brace. Reel can swivel freely on mounting bracket up to 138° or can be locked into place using the locking brace. Up to seven different locking angles can be utilized. Comes standard with all LEVELWIND™ SERIES reels.



L8300-B

Bench & High Wall Mount

Includes a seven position locking brace. Reel can swivel freely on mounting bracket up to 360° or can be locked into place using the locking brace. Up to seven different locking angles can be utilized.

Lead-in Hoses

Part No.	Description
L8305LI	3 ft. lead-in hose for L8305, L8306 & L8310
L8305LI-10	10 ft. lead-in hose for L8305, L8306 & L8310
L8335LI	3 ft. lead-in hose for L8335
L8335LI-10	10 ft. lead-in hose for L8335
L8347LI	3 ft. lead-in hose for L8347, L8344 & L8346
L8347LI-10	10 ft. lead-in hose for L8347, L8344 & L8346
L8349LI	3 ft. lead-in hose for L8349
L8349LI-10	10 ft. lead-in hose for L8349
L8350LI-10	10 ft. lead-in hose for L8350 & L8345
L8363LI	5 ft. lead-in hose for L8363
L8363LI-10	10 ft. lead-in hose for L8363
L8366LI	5 ft. lead-in hose for L8366
L8366LI-10	10 ft. lead-in hose for L8366



LEVELWIND™ SERIES . . .

Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel

GARDEN REEL



ELLS AUTO-REWIND HOSE REELS AUTO-REWIND HOSE REELS

LEVELING HOSE REELS AUTO-LEVELING HOSE REELS AUTO-LEVELING HOSE REELS

The Next Generation of Retractable Hose Reels

Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel Garden Reel

Garden Reels

Model	L8344	L8345	L8346
Application	Garden Reel	Garden Reel	Garden Reel
Hose Size	5/8 I.D. x 60 ft.	1/2 I.D. x 75 ft.	5/8 in. x 50 ft.
Hose Material	P.V.C.	P.V.C.	P.V.C.
Working Pressure	140 PSI	140 PSI	140 PSI
Temp. Range (F°)	40° to 140°	40° to 140°	40° to 140°
Lead-in Hose	3 ft. x 3/4 in.-11 1/2	10 ft. x 3/4 in.-11 1/2	3 ft. x 3/4 in.-11 1/2
	FEMALE GHT BOTH ENDS	FEMALE GHT BOTH ENDS	FEMALE GHT BOTH ENDS
Discharge Hose	3/4 in.-11 1/2 MALE GHT	3/4 in.-11 1/2 MALE GHT	3/4 in.-11 1/2 MALE GHT

Reel inlet: 3/4 in.-11 1/2 MALE GHT

Model	Weight	Package Dimension	Cu. ft.	UPC	Harmonization
L8344	30.3 lb.	19.75 in. x 11.25 in. x 18.75 in.	2.4	0 92329 08344 4	3924.90.55.00
L8345	28.2 lb.	19.75 in. x 11.25 in. x 18.75 in.	2.4	0 92329 08345 1	3924.90.55.00
L8346	24.2 lb.	19.75 in. x 11.25 in. x 18.75 in.	2.4	0 92329 08346 8	3924.90.55.00



Lawn



Garden



Pool



