

800



Standard Configuration Shown

SPRING REWIND REELS

To handle 3/4" or 1" I.D. hose.

- Rollformed channel frame for heavy-duty applications.
- Non sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet 90° balanced pressure swivel joint 1" male BSP threads.
- Standard outlet 1" male BSP threads.
- Pressures to 1000 psi (69 bar).
- Temperatures from -40° F to +250° F (-40° C to +121° C).
- Consult factory for other pressures & temps.
- 4-way roller assembly.
- Constant Tension is available – consult factory.

For:

- Fuel Dispensing
- Air/Water
- Waste Oil Evacuation

Model Number	Hose Capacity			Approx. Weight		Standard Roller Assy	Dimensions***								
	feet			lb.	kg.		in.								
	m.						NET	SHIP	C	E	F	G	X	Y	
	I.D. (in)	3/4"	1"												
	I.D. (mm)	19	25												
	O.D. (in)	1-9/32"	1-9/16"												
	O.D. (mm)	33	40												
816-25-26B		60	35	96	131	R204	10.5	26.12	13.5	25.88	4.5	22			
		18	11	44	59		267	663	343	657	114	559			
818-25-26B		70	50	102	137	R206	10.5	26.12	15.5	25.88	6.5	22			
		21	15	46	62		267	663	394	657	165	559			
820-25-26-10.5A		85	75	131	166	R308	10.5	27	18.25	25.88	8.5	22			
		26	23	59	75		267	686	464	657	216	559			
820-30-31-10.5A		-	100	137	172	R308	10.5	30.5	18.25	31.38	8.5	25.5			
		-	30	62	78		267	775	464	797	216	648			
820-30-31-15.5A		100	-	145	180	R308	15.5	30.5	18.25	31.38	8.5	25.5			
		30	-	66	82		394	775	464	797	216	648			

Notes:

1. Specifications subject to change.
2. Reels models and capacities shown are for standard drag applications; for vertical lift applications consult factory.
3. Other sizes, from standard components, available on request.
4. For a detailed parts breakdown drawing, request ISO 42.
5. **Finish:** refer to Page 4.
6. **Be sure to check dimensions and weights prior to ordering.**

NOTICE: A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

*** x,y indicate mounting holes. See page 2

