

8000**MANUAL OR POWER
REWIND REELS****To handle single 1-1/2" or 2" I.D. hose.**

- Heavy-duty reel designed for longer lengths and larger diameters of hose through 2" I.D.
- Choose gear-driven crank rewind or chain and sprocket drive powered by an electric, hydraulic or compressed air motor.
- Crank rewind reels supplied with a pinion brake, power rewind reels with a comet brake.
- Standard inlet 90° ball bearing swivel joint 2" male BSP threads.
- Standard outlet flanged riser 2" male BSP threads
- Standard inlet, outlet riser and hub assembly are steel. Optional bronze or aluminum swivel joint and stainless steel hub assembly and riser, are available.
- Rollers may be purchased as accessory items.
- Pressures to 600 psi (41 bar).
- Temperatures from -40° F to +175° F (-40° C to +79° C).
- Consult factory for other pressures & temps.

**Shown with Optional
Auxiliary Rewind****For:**

- Bulk Transfer
- Chemical Transfer
- General Dispensing
- Suction/Discharge
(consult factory)

• **Fueling Applications**

Refer to:
Aviation Catalog
H-9448-AVIA
Petroleum Catalog
H-9447-FD



For use on reels with 39" diameter or larger discs and/or when increased torque and slower rewind speeds are required. Factory-installed when specified or available as an accessory item.

Chain Clutch-Reduction Units

8000

Model Number	Hose Capacity of Reel feet m.			Approx. Weight Crank Rewind ³ lb. kg.		Reel Dimensions ^{***} inches mm.					
	I.D. (in) I.D. (mm)	1-1/2" 38	2" 51	NET	SHIP	E	F CRANK	F POWER	G	X	Y
	O.D. (in) O.D. (mm)	2-1/16" 52	2-9/16" 65								
8234-26-27		80	60	120	170	27	33.75	34.75	26.62	18.75	23.25
		24	18	54	77	686	857	883	676	476	591
8238-26-27		100	75	145	195	27	37.75	38.75	26.62	22.75	23.25
		30	23	66	88	686	959	984	676	578	591
8246-26-27		145	100	196	245	27	45.75	46.75	26.62	30.75	23.25
		44	30	89	112	686	1162	1188	676	781	591
8226-33-34		85	60	80	150	31.75	25.25	26.25	33.38	10.25	27.75
		26	18	36	68	806	641	667	848	260	705
8234-33-34		150	115	133	230	31.75	33.75	34.75	33.38	18.75	27.75
		46	35	60	105	806	857	883	848	476	705
8238-39-40		340	225	218	420	40	37.75	38.75	39.88	22.75	37
		104	69	99	191	1016	959	984	1013	578	940

Notes:

- Specifications subject to change.
- Upon request, reels can be supplied with drum lengths other than shown and with disc sizes in other diameters.
- Weights shown in chart are for crank rewind models. ADD these amounts for power rewind models:

	Net (lbs.)	Ship (lbs.)	Net (kg.)	Ship (kg.)
Electric	40	40	18.1	18.1
Hydraulic	20	20	9.1	9.1
Air	20	20	9.1	9.1

- When ordering power rewind models, prefix model number with:
 A = Air Rewind EP = Electric Rewind (1/2 HP)
 HD = Hydraulic Rewind
 (Air rewind reels are supplied with control valve and hose; 12v and 24v DC rewind reels are supplied with switch and solenoid; 115v AC rewind reels are not supplied with switch but can be ordered separately; hydraulic rewind reels are not supplied with control valve.)

5 For a detailed parts breakdown drawing, request ISO 35.

6. **Finish:** refer to Page 4.

7. Be sure to check dimensions and weights prior to ordering.

NOTICE: A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

*** x,y indicate mounting holes. See page 2

