

9000**MANUAL OR POWER
REWIND REELS****To handle 2" through 3" I.D. hose.**

- Heavy-duty reel designed for longer lengths and larger diameters of hose through 3" I.D.
- Choose gear-driven crank rewind or chain and sprocket drive powered by an electric, hydraulic or compressed air motor.
- Crank rewind reels supplied with a pinion brake power rewind reels with a comet brake.
- Standard inlet 90° ball bearing swivel joint 3" male BSP threads.
- Standard outlet flanged riser 3" male BSP threads.
- Standard, outlet riser and hub assembly are aluminum with ductile inlet. Optional bronze or aluminum swivel joint and stainless steel hub assembly and riser, are available.
- Rollers may be purchased as accessory items.
- Pressures to 300 psi (21 bar).
- Temperatures from -20° F to +225° F (-29° C to +107° C).
- Consult factory for other pressures & temps.

**Shown with Optional
Auxiliary Rewind****For:**

- Suction/Discharge
(consult factory)
- High Volume
Application
- Bulk Transfer
- Chemical Transfer

- **Fueling Applications**

Refer to:
Aviation Catalog
H-9448-AV
Petroleum Catalog
H-9447-FD



For use on reels with 39" diameter or larger discs and/or when increased torque and slower rewind speeds are required. Factory-installed when specified or available as an accessory item.

Chain Clutch-Reduction Units



Model Number	Hose Capacity of Reel feet m.				Approx. Weight Crank Rewind ³ lb. kg.		Reel Dimensions** inches mm.					
	I.D. (in) I.D. (mm)	2" 51	2-1/2" 64	3" 76	NET	SHIP	E	F CRANK	F POWER	G	X	Y
	O.D. (in) O.D. (mm)	2-9/16" 65	3-3/16" 81	3-3/4" 95								
For Power Rewind See Note 4												
9332-33-34		70 21	30 9	25 8	147 67	217 98	31.75 807	33.75 857	33.25 845	33.88 861	16.25 413	27.75 705
9338-33-34		100 30	45 14	35 11	187 85	257 117	31.75 807	40.25 1022	39.75 1010	33.88 861	22.75 578	27.75 705
9346-33-34		140 43	60 18	50 15	237 108	372 169	31.75 807	48.25 1226	47.75 1213	33.88 861	30.75 781	27.75 705
9338-39-40		185 56	90 27	80 24	239 108	480 218	40 1016	40.25 1022	39.75 1010	40.38 1026	22.75 578	37 940
9334-45-46		200 61	130 40	115 35	361 164	525 239	46 1168	36.25 921	35.75 908	46.38 1178	18.75 476	43 1092

Notes:

- Specifications subject to change.
- Upon request, reels can be supplied with drum lengths other than shown and with disc sizes in other diameters.
- Weights shown in chart are for crank rewind models. ADD these amounts for power rewind models:

	Net (lbs.)	Ship (lbs.)	Net (kg.)	Ship (kg.)
Electric	40	40	18.1	18.1
Hydraulic	20	20	9.1	9.1
Air	20	20	9.1	9.1

- When ordering power rewind models, prefix model number with:
A = Air Rewind EP = Electric Rewind (1/2 HP)
HD = Hydraulic Rewind
(Air rewind reels are supplied with control valve and hose; 12v and 24v DC rewind reels are supplied with switch and solenoid; 115v AC rewind reels are not supplied with switch but can be ordered separately; hydraulic rewind reels are not supplied with control valve.)

5. For a detailed parts breakdown drawing, request ISO 57.

6. **Finish:** refer to Page 4.

7. Be sure to check dimensions and weights prior to ordering.

NOTICE: A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

*** x,y indicate mounting holes. See page 2

