

AT1200

PORTABLE HOSE REELS ON WHEELS

To handle 1/2" through 1" I.D. hose.

- Continuous flow reels with swivel joint inlet, fluid hub, outlet riser.
- Comes with pneumatic tires and spring tension brake.
- Direct crank rewind.
- One-piece foot, rubber tires, and removable steel handlebar.
- Permanently attached crank.
- Model AT1200 –standard inlet 90° balance pressure swivel joint 1" male BSP threads.
- Standard outlet is 1" male BSP threads.
- Prefix GH to model number when ordering garden hose thread, e.g., GHAT1200.
- Operates at pressures to 1000 psi.
- Temperatures from -40° F to +250° F (-40° C to +121° C).
- Consult factory for other pressures & temps.



GHAT 1200 Configuration Shown

For:

- Grounds Maintenance
- Restaurants/Hotels
- Home Use

Model Number	Hose Capacity of Reel					Approx. Weight	
		feet				NET	SHIP
		m.					
	I.D. (in)	1/2"	5/8"	3/4"	1"		
	I.D. (mm)	13	16	19	25		
	O.D. (in)	7/8"	1"	1-9/32"	1-9/16"		
	O.D. (mm)	22	25	33	40		
AT1200		350	250	150	100	86	91*
		107	76	46	30	39	41

Notes:

1. Specifications subject to change.
 2. For a detailed parts breakdown drawing, request ISO 87.
 3. **Finish:** refer to Page 4.
 4. **Be sure to check dimensions and weights prior to ordering.**
- *When shipped as a parcel package (via Fed-Ex or UPS Ground)

