

C3200

MANUAL REWIND STORAGE REELS

To handle single 1/2" through 1-1/2" O.D.

- A 4-1/2" x 9" (114mm x 229mm) opening in the drum to initiate winding.
- Designed for storage of long lengths of hose, cable, rope, wire or other materials.
- Choose disc rewind or removable direct crank rewind.
- Supplied with spring actuated pin lock.
- Optional divider discs can be placed at almost any point. Be sure to specify spacing of discs on your order.
- Rollers may be purchased as accessory items.



Standard Configuration Shown

Optional Crank Handle

For Storage Of:

- Hose
- Cable
- Rope
- Wire

Model Number	Hose Capacity of Reel feet m.						Approx. Weight Crank Rewind lb. kg.		Reel Dimensions*** inches mm.			
	O.D. (in) O.D. (mm)	1/2"	3/4"	1"	1-1/4"	1-1/2"	NET	SHIP	E CRANK	F CRANK	G	X
C3218-25-26	13 305	1000 305	450 137	225 69	125 38	90 27	85 39	127 58	25.5 648	22 559	27.88 708	7 178
C3228-25-26	-	-	1000 305	500 152	325 99	200 61	109 49	151 68	25.5 648	32.5 826	27.88 708	17.5 445
C3234-25-26	-	-	1300 396	650 198	400 122	275 84	122 55	164 74	25.5 648	38.5 978	27.88 708	23.5 597
C3246-25-26	-	-	-	975 297	625 191	400 122	149 68	199 90	25.5 648	50.5 1283	27.88 708	35.5 902
C3228-30-31	-	-	-	900 274	525 160	375 114	120 54	170 77	28.75 730	32.5 826	29.88 759	17.5 445
C3234-30-31	-	-	-	1100 335	675 206	500 152	133 60	183 83	28.75 730	38.5 978	29.88 759	23.5 597
C3224-33-34	-	-	-	750 229	475 145	350 107	120 54	170 77	31.75 806	28 711	32.38 822	13 330
C3246-33-34	-	-	-	-	1200 366	925 282	170 77	248 112	31.75 806	50.5 1283	32.38 822	35.5 902

Notes:

1. Specifications subject to change.
2. Upon request, reels can be supplied with drum lengths other than shown and with disc sizes in other dimensions.
3. Dimensions reflect pressed frames.
4. For a detailed parts breakdown drawing, request ISO 117.
5. Series C3200 requires 3-1/2" clearance to remove crank handle.
6. Subtract 5" from 'F' dimension for disc rewind on C3200 Series.
7. **Finish:** refer to Page 4.
8. **Be sure to check dimensions and weights prior to ordering.**

*** x,y indicate mounting holes. See page 2

