

SS4000

MANUAL REWIND REELS

To handle single 3/4" or 1" I.D. hose.

- Lightweight compact reels designed for long lengths of hose.
- Direct crank rewind is removable.
- Cam-lock brake, spring actuated pin lock.
- Standard inlet 90° ball bearing swivel joint 1" female NPT threads.
- Standard outlet 1" female NPT threads.
- Rollers and roller mounting brackets are accessory items. Specify roller position.
- Pressures to 1000 psi (69 bar).
- Temperatures from +20° F to +400° F (-7° C to +204° C).
- Consult factory for other pressures & temps.



For:

- Food Processing
- Bottling Plants
- Fire Protection
- Water Supply
- Chemical Transfer

Parts Drawing – ISO 178

Model Number	Hose Capacity of Reel feet m.			Approx. Weight Crank Rewind lb. kg.		Reel Dimensions*** inches mm.				
	I.D. (in) I.D. (mm)	3/4" 19	1" 25	NET	SHIP	A	B	E	F	X
	O.D. (in) O.D. (mm)	1-9/32" 33	1-9/16" 40							
SS4018-17-18		50 15	35 11	36 16	50* 23	15 381	10 254	16.5 419	27 686	13.5 343
SS4024-17-18		100 30	50 15	46 21	56* 25	21 533	16 406	16.5 419	33 838	19.5 495
SS4030-17-18		150 46	75 23	57 26	62* 28	27 686	22 559	16.5 419	39 991	25.5 648
SS4038-17-18		200 61	100 30	70 32	112 51	35 889	30 762	16.5 419	47 1194	33.5 851

Notes:

1. Specifications subject to change.
2. Upon request, reels can be supplied with drum lengths other than shown.
3. Dimension "F" is the overall length of standard model reels. Crank rewind reels require 3-1/2" clearance to remove or install crank handle.
4. **Finish:** refer to Page 2.
5. **Be sure to check dimensions and weights prior to ordering.**

NOTICE: A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

* When shipped as a parcel package (via Fed-Ex or UPS Ground).
 *** x,y indicate mounting holes. See page 2

