

SS800

SPRING REWIND REELS

To handle 3/4" or 1" I.D. hose.



Standard Configuration Shown with Optional Polished Finish

For:

- Dairy
- Caustic Materials

- Air/Water
- Chemical/Food Transfer

- Square tubing frame for heavy-duty applications.
- Non sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet 90° ball bearing swivel joint 1" female NPT threads.
- Standard outlet 1" female NPT threads.
- Pressures to 1000 psi (69 bar).
- Temperatures from +20° F to +400° F (-7° C to +204° C).
- Consult factory for other pressures & temps.
- 4-way roller assembly.
- Constant Tension is available – consult factory.

Parts Drawing – ISO 198

Model Number	Hose Capacity			Approx. Weight		Standard Roller Assy	Reel Dimensions***									
	I.D. (in) I.D. (mm)	feet m.		NET	SHIP		A	B	C	D	E	F	G	H	X	Y
		1-9/32" 33	1-9/16" 40													
SS816-25-26B	3/4" 19	35 11	1" 25	96 44	131 59	R204S	9.25 235	4 102	10.5 267	25 635	26.12 663	13.5 343	25.88 657	13.5 343	4.5 114	22 559
SS818-25-26B	7/8" 21	50 15	1-1/8" 30	102 46	137 62	R206S	11.25 286	6 152	10.5 267	25 635	26.12 663	15.5 394	25.88 657	13.5 343	6.5 165	22 559
SS820-25-26-10.5A	1" 26	75 23	1-1/4" 33	131 59	166 75	R308S	13.25 337	8 203	10.5 267	25 635	27 686	18.25 464	25.88 657	13.5 343	8.5 216	22 559
SS820-30-31-10.5A	1-1/8" 33	100 30	1-5/8" 40	137 62	172 78	R308S	13.25 337	8 203	10.5 267	28.5 724	30.5 775	18.25 464	31.38 797	17 432	8.5 216	25.5 648
SS820-30-31-15.5A	1-1/4" 33	100 30	1-5/8" 40	145 66	180 82	R308S	13.25 337	8 203	15.5 394	28.5 724	30.5 775	18.25 464	31.38 797	17 432	8.5 216	25.5 648

Notes:

1. Specifications subject to change.
2. Reels models and capacities shown are for standard drag applications; for vertical lift applications consult factory.
3. Other sizes, from standard components, available on request.
4. **Finish:** refer to Page 2.
5. **Be sure to check dimensions and weights prior to ordering.**

NOTICE: A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

* When shipped as a parcel package (via Fed-Ex or UPS Ground).
 *** x,y indicate mounting holes. See page 2

