

# SSN800

## SPRING REWIND REELS

To handle 3/4" or 1" I.D. hose.

- Standard N series has a narrow frame and compact mounting base.
- Non sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet 90° ball bearing swivel joint 1" female NPT threads.
- Standard outlet 1" female NPT threads.
- Pressures to 1000 psi (69 bar).
- Temperatures from +20° F to +400° F (-7° C to +204° C).
- Consult factory for other pressures & temps.
- 4-way roller assembly
- Constant Tension is available – consult factory.



Shown with Optional Polished Finish

For:

- Dairy
- Caustic Materials

- Air/Water
- Chemical/Food Transfer

### Parts Drawing – ISO 173

Model Number	Hose Capacity			Approx. Weight		Standard Roller Assy	Reel Dimensions***							
	feet			lb.	kg.		in.							
	m.						mm							
I.D. (in) I.D. (mm)	3/4" 19	1" 25		NET	SHIP	A	B	C	E	F	G	H	X	
SSN816-19-20J	25 8	15 5	75 34	91* 41	N204S	10 254	4 102	10.5 267	20.75 527	14 356	20 508	10.62 270	8 203	
SSN818-23-24J	50 15	25 8	87 39	100 45	N206S	12 305	6 152	10.5 267	23.75 603	15 381	24 610	12.62 321	10 254	
SSN816-25-26B	60 18	35 11	96 44	131 59	N204S	10 254	4 102	10.5 267	25.25 641	14 356	26 660	13.62 346	8 203	
SSN818-25-26B	70 21	50 15	102 46	137 62	N206S	12 305	6 152	10.5 267	25.25 641	16 406	26 660	13.62 346	10 254	

**Notes:**

1. Specifications subject to change.
2. Reel models and capacities shown are for standard drag applications; for vertical lift applications consult factory.
3. Other sizes, from standard components, available on request.
4. **Finish:** refer to Page 2.
5. **Be sure to check dimensions and weights prior to ordering.**

**NOTICE:** A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

\* When shipped as a parcel package (via Fed-Ex or UPS Ground).  
 \*\*\* n/x, n/y indicate mounting holes. See page 2

