

# 

# **LEVELWIND™ TECHNOLOGY**

Automatically layers the hose back and forth across the reel.

# **LATCHING MODE SWITCH**

Latch hose every three feet for extended use or switch to free run for immediate, automatic rewinding.



## **Retractable Air Hose Reels with Levelwind™ Technology**



PRO

Featuring Levelwind™ – Flexzilla's unique winding system that automatically layers hose back and forth across the reel ensuring that the hose is coiled smoothly, easily...every time – and includes Flexzilla® air hose and lead-in hose.





### **FEATURES:**

- Latching Mode Switch Choose from latching hose every 3 ft. for extended use or switch to free run for immediate automatic rewinding
- Seven Position Locking Bracket These reels can swivel freely on a
  mounting bracket up to 135° or can be
  locked into place using the locking brace.
  Up to seven different locking angles can
  be utilized (L8300-W)
- Adjustable Hose Stopper Increase or decrease the length of the hose that remains when hose is fully retracted
- Extra Large Swivel A 3/4 in. swivel reduces flow restrictions and allows for maximum flow
- Freestanding Base Portable Use freestanding or mounted on wall or ceiling. Flat base allows reel to rest on the ground
- Built-In Handle For carrying ease
- Durable Construction Made from durable UV stabilized polypropylene
- Hose Material Flexible Hybrid Polymer
- Lead-in Hose Included 5 ft.



Part No.	Hose I.D.	Hose Length	Working Pressure @ 70°F	Temperature Range (F°)	Lead-in Hose Connection	Reel Inlet	Hose Outlet	Weight	Retail Packaging	Assembled in USA
L8305FZ	3/8 in.	50 ft.	300 psi	-40° to 140°	3/4 in. Female GHT x 1/4 in. MNPT	3/4 in. – 11½ Male GHT	1/4 in. MNPT	25 lbs.	•	
L8306FZ	3/8 in.	75 ft.	300 psi	-40° to 140°	3/4 in. Female GHT x 1/4 in. MNPT	3/4 in. – 11½ Male GHT	1/4 in. MNPT	30 lbs.	•	•
L8335FZ	1/2 in.	50 ft.	300 psi	-40° to 140°	3/4 in. Female GHT x 3/8 in. MNPT	3/4 in. – 11½ Male GHT	3/8 in. MNPT	29 lbs.	•	

# **Mounting Brackets**

### **L8300-B FEATURES:**

- · Includes a seven position locking bracket
- Reel can swivel freely on mounting bracket up to 360° or can be locked into place using the locking brace
- · Mounting options: high wall or bench

### **L8300-W FEATURES:**

- Includes a seven position locking bracket
- Reel can swivel freely on mounting bracket up to 135° or can be locked into place using the locking brace
- · Mounting options: wall or overhead ceiling





# **NEW** Retractable Air Hose Reels



These economical, retractable air hose reels are ideal for the home shop.



HOSE I.D.	WORKING PRESSURE
3/8 IN.	150 PSI



HOSE I.D.	WORKING PRESSURE
3/8 IN.	150 PSI

### **L8232FZ FEATURES:**

- Automatic Leveling System Layers the hose evenly when rewinding
- Multipoint Latch Mechanism Reel will automatically lock hose in place at any length wherever you stop
- Impact Resistant Housing
- Speed Control Device Provides consistent and safe speed when retracting the hose
- Adjustable Hose Stopper Increase or decrease the length of the hose that remains when hose is fully retracted
- Swivel Mounting Bracket Pivots in the direction of your work, reel can be mounted to wall or ceiling
- Lead-in Hose Included 3 ft. x 1/4 in. MNPT

### **L8250FZ FEATURES:**

- Multi-Position Release Ratchet Allows appropriate amount of hose to be extended for each jobsite
- Auto Retract/Latch Hose Mechanism Simplifies every job by keeping excess hose out of the work space
- Positive Latching Mechanism Locks hose automatically in 18 in. intervals
- Durable Construction Made from durable UV stabilized polypropylene
- Adjustable Hose Stopper Increase or decrease the length of the hose that remains when hose is fully retracted
- Swivel Mounting Bracket Pivots in the direction of your work, reel can be mounted to wall or ceiling
- Lead-in Hose Included 3 ft. x 1/4 in. MNPT

### **Retractable Air Hose Reels**

Part No.	Hose I.D.	Hose Length	Working Pressure @ 70°F	Temperature Range (F°)	Lead-in Hose Connection	Hose Outlet	Weight	Retail Packaging
L8232FZ	3/8 in.	30 ft.	150 psi	-40° to 140°	1/4 in. MNPT	1/4 in. MNPT	13 lbs.	•
L8250FZ	3/8 in.	50 ft.	150 psi	-40° to 140°	1/4 in. MNPT	1/4 in. MNPT	17 lbs.	•